


a richiesta disponibili anche Brunite o senza Punta

sim. ISO 7049 - DIN 7981 H

# Tapping screws

pan head with cross recess H (Phillips), type C (with cone point)



dk k min.	4,2	5,6	6,9	7,5	8,2	9,5	10,8	12,5
k max.	1,55	1,95	2,35	2,55	2,75	3,25	3,65	4,25
r max.	1,80	2,20	2,60	2,80	3,05	3,55	3,95	4,55
⊕	P1	P1	P2	P2	P2	P2	P3	P3
Length / Ø	ST2,2	ST2,9	ST3,5	ST3,9	ST4,2	ST4,8	ST5,5	ST6,3
4,5 (1/4")	▲●							
6,5 (1/4")	▲●	▲●	▲●	▲●	▲●			
9,5 (3/8")	▲●	▲●	▲●	▲●	▲●	▲●	▲●	
13 (1/2")	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
16 (5/8")	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
19 (3/4")	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
22 (7/8")	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
25 (1")	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
32 (1 1/4")	▲●	▲●	▲●	▲●	▲●	▲●	▲●	▲●
38 (1 1/2")		▲●	▲●	▲●	▲●	▲●	▲●	▲●
45 (1 3/4")			▲●	▲●	▲●	▲●	▲●	▲●
50 (2")			▲●	▲●	▲●	▲●	▲●	▲●
55 (2 1/8")			▲●	▲●	▲●	▲●	▲●	▲●
60 (2 3/8")			▲●	▲●	▲●	▲●	▲●	▲●
70 (2 3/4")			▲●	▲●	▲●	▲●	▲●	▲●
80 (3 1/8")				▲●	▲●	▲●	▲●	▲●
90 (3 1/2")					▲●	▲●	▲●	▲●
100 (4")					▲●	▲●	▲●	▲●
120 (4 3/4")						▲●	▲●	▲●
SU	1000	1000	1000 ≥ 32 500	1000 ≥ 32 500	1000 ≥ 32 500 ≥ 50 200	1000 ≥ 22 500 ≥ 32 100	500 ≥ 32 100	200 ≥ 32 100

■ A1 / ▲ A2 / ● A4 | SU: Sales units | All measurements in mm / inch | Other dimensions on request.

Example item no. 7981-2-4,2X38 DIN 7981 - A2 - Ø 4,2mm - l = 38mm - phillips drive